

US007231063B2

(12) United States Patent

Naimark et al.

(10) Patent No.: US 7,231,063 B2

(45) **Date of Patent:** Jun. 12, 2007

(54) FIDUCIAL DETECTION SYSTEM

(75) Inventors: **Leonid Naimark**, Brookline, MA (US); **Eric Foxlin**, Arlington, MA (US)

(73) Assignee: InterSense, Inc., Bedford, MA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 676 days.

(21) Appl. No.: 10/215,503

(22) Filed: Aug. 9, 2002

(65) Prior Publication Data

US 2004/0028258 A1 Feb. 12, 2004

(51) Int. Cl. G06K 9/00 (2006.01)

202/102 240/

(52) **U.S. Cl.** **382/103**; 348/169

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,553,438 A	1/1971	Blitz
3,971,917 A	7/1976	Maddox et al.
5,521,843 A *	5/1996	Hashima et al 700/253
5,832,139 A	11/1998	Batterman et al.
5,856,844 A *	1/1999	Batterman et al 348/207.99
6,064,749 A *	5/2000	Hirota et al 382/103
6,681,031 B2 *	1/2004	Cohen et al 382/103

FOREIGN PATENT DOCUMENTS

WO 98/54593 12/1998

OTHER PUBLICATIONS

Gatrell, L., Hoff, W. and Sklair, C., "Robust Image Feature: Concentric Contrasting Circles and Their Image Extraction", SPIE Proceedings, Cooperative Intelligent Robotics in Space II, 1991, Boston

Sklair, C., Hoff, and Gatrell, L., "Accuracy of Locating Circular Features Using Machine Vision", SPIE Proceedings, Cooperative Intelligent Robotics in Space II, 1991, Boston.

Hoff, W., Nguyen, K. and Lyon, T., "Computer Vision-based registration techniques for augmented reality", Proceedings of IRCV, SPIE vol. 2904, 1996, Boston.

Neumann, U. and Cho, Y., "A Self-tracking Augmented Reality System", Proceedings of ACM VRST, 1996.

(Continued)

Primary Examiner—Samir Ahmed Assistant Examiner—Abolfazi Tabatabai (74) Attorney, Agent, or Firm—Fish & Richardson P.C.

(57) ABSTRACT

A new fiducial design allows having thousands of different codes. These fiducials are printed on a standard black-and-white (or color) printer and easily could be mounted on a walls, ceiling and objects in a room. The design includes "solid" outside mono-color ring and 2-D dense inside coding scheme. Image processing algorithms are implemented in Smart Camera with a built-in DSP to run all required image-processing tasks. A tracking system implementation includes an inertial measurement unit and one outward-looking wide-angle Smart Camera with possible extensions to number of stationary inward-looking cameras. The system operates in various real-world lighting conditions without any user intervention due to homomorphic image processing processes for extracting fiducials in the presence of very non-uniform lighting.

33 Claims, 9 Drawing Sheets

